



# VENGA 2016 Specifications

EXTERIOR FEATURES	L	EX
15" Steel wheels	X	
16" Alloy wheels		X
ISG and Low Rolling Tyres	X	
Temporary steel wheel	X	X
Privacy glass(rear)		X
Tinted glass (front)	X	X
Daytime Running Lights LED	-	X
Body coloured bumper	X	X
Body coloured door handles & mirrors	X	X
Electrically adjustable & heated door mirrors	X	X
Rear spoiler with mounted stop light	X	X
Headlamp levelling device	X	X
Front variable intermittent wipers	X	X
Rear one speed wipers	X	X
Front fog lamp		X
Rear fog lamp	X	X
INTERIOR FEATURES		
Power steering	X	X
Drivers seat height adjust	X	X
Tilt & telescopic adjustable steering wheel	X	X
Poly Urethane steering wheel & gearshift	X	
Leather steering wheel & gearshift		X
Black cloth upholstery	X	X
Metallic centre fascia	X	X
Metallic parking button, interior door handle & air vent knob		X
Assist grips	X	X
Rear coat hook (x1) & front shopping hook (x1)	X	X
Front console 12v power socket (x2)	X	X
Luggage area 12v power socket	X	X
Luggage under floor tray	X	X
Luggage net hook & luggage net	X	X
Sunvisor with ticket holders	X	X
Illuminated vanity mirrors & map lamps	X	X
Seat back pockets	X	X
Glove box	X	X
Mud flaps	X	X
Heated rear window with timer	X	X



The Power to Surprise



# VENGA 2016 Specifications

INTERIOR FEATURES CONT.	L	EX
Drivers seat & rear centre armrest	X	X
60:40 Split back folding, sliding & double clinging seats	X	X
External temperature display	X	X
Plastic foot rest	X	X
AUDIO		
Radio & CD & MP3 & RDS	X	X
AUX, USB & IPOD cable	X	X
Audio control on steering wheel	X	X
Bluetooth & voice recognition*	-	X
Roof type antenna	X	X
6 speaker	X	X
SAFETY & SECURITY		
Central door lock/unlock (incl impact sensor unlock)	X	X
Alarm & folding key	X	X
6 airbags	X	X
Up & down head restraints with active headrest	X	X
Impact sensing auto door unlocking	X	X
Front 15" disc brake	X	X
ABS & BAS	X	X
ESP & HAC	X	X
Seat belt warning	X	X
Parking brake warning	X	X
Child safety rear door lock	X	X
Seat belt height adjust	X	X
Immobiliser	X	X
ISOFIX top tethers & lower anchor points	X	X
Back warning sensor		X
VENTILATION & VISIBILITY		
Manual air conditioner	-	X
4- speed ventilation fan	X	X
Rheostat	X	X
Front electric windows (drivers auto down)	X	
Front & rear electric windows (drivers auto up/down)		X
Day & night rear view mirror	X	X
Front, centre cabin & luggage area lamps	X	X



The Power to Surprise



# VENGA 2016 Specifications

ENGINE		1.4 Gasoline 5 M/T	1.6 Gasoline 6 A/T	1.4 Diesel 6 M/T
Displacement (cc)		1,396	1591	1396
Bore x stroke (mm)		77 X 74.99	77 X 85.44	75.0 X 79.0
Compression ratio		10.5	10.5	16
Max. power (ps @ rpm)		90 @ 6,000	125 @ 6,300	90 @ 4000
Max. power (kw @ rpm)		66.2 @ 6,000	91.5 @ 6,300	66 @ 4000
Max. torque (kg.m @ rpm)		14.0 @ 4,000	15.9 @ 4,200	24.5 @ 1500-2500
Max. torque (N.m @ rpm)		137.3 @ 4,000	156.0 @ 4,200	240 @ 1500-2500
Ignition system		Stick Coil (24.5)		Compression Ignition
Intake system		TIS		WGT
Valve system		16 Valve MLA		16 Valve HLA
Fuel system	Injector	EV6 Short (4-Hole 2-Spray), 137g/min, 15 degree		Common Rail (Bosch) 2,000bar
	Fuel Rail	Pipe - SUS		
Emission control system		EU6 : WCC+UCC		EU5,6 : CC LNT DPF EU4 : WCC
Electric system	Battery (AH)	36 AH		54AH
	Alternator	13.5V 90A 13.5V 110A (ISG)		13.5V, 130A
	Starter	12V 0.9kw 12V 1.3kw (ISG)		ISG : 12V, 1.8KW NON-ISG : 12V, 1.7KW
Lubricant oil capacity (liter)		3.3 (with Oil filter)		5.3 (with Oil filter)
Transmission				
Drive Type		FF	FF	FF
Drive System		5 Speed	6 Speed	6 Speed
Gear ratio	1st	3.769	4.400	3.769
	2nd	2.045	2.726	2.040
	3rd	1.370	1.834	1.294
	4th	1.036	1.392	0.905
	5th	0.839	1.000	0.702
	6th	-	0.774	0.596
	Reverse	3.545	3.440	3.583
Final gear ratio (FGR)		4.267 / 4.400	3.612	3.941
Clutch Type		Dry Single Plate Diaphragm Spring Type	Torque Converter	Dry Single Plate Diaphragm Spring Type
Lubricant oil capacity (liter)		1.9-2.0	7.3	1.7-1.8



The Power to Surprise



# VENGA 2016 Specifications

ENGINE	1.4 Gasoline 5 M/T	1.6 Gasoline 6 A/T	1.4 Diesel 6 M/T
<b>STEERING WHEEL</b>			
Type	Rack & Pinion / MDPS (Motor Driven Power Steering)		
Overall steering gear ratio	11.8		
Steering wheel turn (lock to lock)	2.77		
Minimum turning radius (m)	5.21		
<b>BRAKES</b>			
General	Hydraulically Operated by Dual Cross System		
Front brake size	Disc Brake - 15" (Φ280X26t)		
Rear brake size	Disc Brake - 14" (Φ258X10t)		
Vacuum Booster	Diameter (inch)	10"	
	Booster ratio	8:1	
Master Cylinder	Type	Fixed Seal / Fixed Seal	
	Diameter (inch)	0.874"	
<b>WEIGHT</b>			
Curb Weight Minimum (Kg)	1,178	1,222	1270
Curb Weight Maximum (Kg)	1,268	1,335	1,370
Gross vehicle weight (kg)	1,710	1,780	1800
<b>DIMENSION</b>			
<b>Exterior (mm)</b>			
Overall Length	4,075		
Overall Width	1,765		
Overall Height	1,600		
Wheelbase	2,615		
Wheel Tread (Front / Rear)	1,553 / 1,557 (195/65R15) & 1,547 / 1,551 (205/55R16) & 1,541 / 1,545 (205/50R17)		
Overhang (Front / Rear)	792 / 668		
<b>Interior (mm)</b>			
Leg room (Front / Rear)	1,080 / 901		
Head room (Front / Rear)	1,020 / 980		
Shoulder room (Front / Rear)	1,388 / 1,367		
Minimum Ground Clearance (mm)	156		
Minimum Turning Ratio (m)	5		
Boot Capacity (liter, VDA211)	440		
Fuel Tank Capacity (liter)	50		



The Power to Surprise

Please note that whilst every care has been taken to ensure that these specifications are current and correct, occasionally specification changes occur that may not be reflected in this document. Please check in the showroom and with your dealer that your chosen model has your required specification.



# VENGA 2016 Specifications

		1.4 Gasoline 5 M/T	1.6 Gasoline 6 A/T	1.4 Diesel - High 6 M/T
<b>DYNAMIC PERFORMANCE</b>				
Max speed (kph)		168/169	180.0	167.0
Acceleration (sec)	0 – 100kph	12.8/12.7	11.5	14.2
	0 – 130kph	23.5/23.5	20.2	24.3
	80 – 120kph	18.3/17.4	9.4	13.0
	120 – 140kph	12.8/12.2	7.3	12.0
Brake 100 – 0kph (m) (AMS)		37.0m		
<b>FUEL CONSUMPTION (Standard)</b>				
Fuel economy				
Urban (liter/100km)		6.6	8.6	5.2
Extra Urban (liter/100km)		5.1	5.2	3.9-
Combined (liter/100km)		5.6	6.5	4.4
CO <sub>2</sub>				
Urban (g/km)		152.0	200	137
Extra Urban (g/km)		117.0	121	102
Combined (g/km)		"130 (15/16" LRR): Continental"	"150 (15/16" LRR): Continental"	115 (15/ 17" silica & 16" LRR conti)



The Power to Surprise

Please note that whilst every care has been taken to ensure that these specifications are current and correct, occasionally specification changes occur that may not be reflected in this document. Please check in the showroom and with your dealer that your chosen model has your required specification.